

STANDARD FOR
BROADBAND BURIED SERVICE WIRE,
FILLED, POLYOLEFIN INSULATED, COPPER CONDUCTOR
TECHNICAL REQUIREMENTS

Published By

INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Post Office Box 1568

Carrollton, GA 30112, U.S.A.

© 2011 by ICEA

Approved 11/28/2011 by
Insulated Cable Engineers Association, Inc.

Approved 5/15/2012 by
American National Standards Institute, Inc.

Copyrighted by the ICEA
Contents may not be reproduced
in any form without permission of the
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

IHS
15 Inverness Way East
Englewood, CO 80112-5776 USA
Telephone: (800) 854-7179
www.ih.com

Note: The user's attention is called to the possibility that compliance with this document may require use of one or more inventions covered by patent rights.

By publication of this Document, no position is taken with respect to the validity of those claims or of any patent rights in connection therewith. The patent holder(s) so far identified have, however, filed statements of willingness to grant licenses under those rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such licenses. Details may be obtained from the standards developer.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgements contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgement or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

FOREWORD

ICEA Standards are published in the public interest and are intended to promote product uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to the Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of service wires made in conformity with this Standard. This Standard hereafter assumes that the manufacture, testing, installation, and maintenance of service wires defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions of interpretation of ICEA Standards can only be accepted in writing, and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to:

Secretary
Insulated Cable Engineers Association
P.O. Box 1568
Carrollton, GA 30112
United States of America

This Standard was developed by the ICEA Communications Cable Division, Working Group 704. It was approved by ICEA on November 28, 2011.

The members of the ICEA Working Group 704, who participated in this project, were:

WG Chairman: Peter Fraley

D. K. Baker

R Gould

G. L. Dorna

TABLE OF CONTENTS

CONTENTS: SECTION	PAGE
SECTION 1 GENERAL	1
1.1 Purpose.....	1
1.2 Scope.....	1
1.3 Options and Information	1
1.4 Units and Tolerances	2
1.5 References.....	2
1.6 Quality Assurance	2
1.7 Safety Considerations	3
SECTION 2 CONDUCTORS	3
2.1 Requirements.....	3
2.2 Factory Joints.....	4
SECTION 3 CONDUCTOR INSULATION	4
3.1 Insulation Material	4
3.2 Insulation Type.....	4
3.3 Insulation Dimensions, Colors, and Splices	4
3.4 Insulation Physical Requirements	5
3.4.1 Adhesion.....	5
3.4.2 Elongation.....	5
3.4.3 Compression.....	5
3.4.4 Cold Bend	6
3.4.5 Shrinkback.....	6
3.4.6 Thermal Oxidative Stability	6
3.5 Twist Length and Color Coding	6
SECTION 4 CORE CONSTRUCTION	7
4.1 Core Layup.....	7
4.2 Binders	7
4.3 Core Wrap.....	7
4.4 Filling Compound	7
4.4.1 Filling Compound Type.....	7
4.4.2 Adequacy of Fill	8
4.5 Flooding Compound.....	8
4.6 Water Swellable Materials.....	8
4.7 Rip Cord(s).....	8

TABLE OF CONTENTS

CONTENTS: SECTION	PAGE
SECTION 5 SHIELDS.....	8
5.1 Shielding System	8
5.1.1 Gopher Shields	8
5.1.2 Non-Gopher Shields	9
5.2 Shield Materials.....	9
5.2.1 5- or 6-Mil Copper Clad Stainless Steel Tape.....	9
5.2.2 5- or 6-Mil Copper Clad Alloy Steel Tape	9
5.2.3 6-Mil C195 Copper Alloy Tape.....	9
5.2.4 7-Mil C194 Copper Alloy Tape.....	9
5.2.5 4- or 5-Mil C220 Copper Alloy Tape	9
5.2.6 5-mil C230 Copper Alloy Tape.....	10
5.2.7 8-Mil Coated Aluminum Tape	10
5.3 Shield Application.....	10
5.4 Shield Corrugation	10
5.5 Shield Overlap.....	10
5.6 Shield Splices.....	10
SECTION 6 INNER AND OUTER JACKET, ARMORING SYSTEMS	11
6.1 Inner Jacket.....	11
6.1.1 Material and Test Requirements.....	11
6.1.2 Inner Jacket Thickness Requirements	11
6.2 Outer Jacket.....	11
6.2.1 Raw Material.....	11
6.2.2 Outer Jacket Thickness Requirements	12
6.2.3 Completed Wire Material Requirements	12
6.2.4 Shrinkback.....	13
6.3 Armoring Systems.....	13
6.3.1 6-Mil Bare Steel Tape	13
6.3.2 6-Mil Coated Steel Tape	13
6.4 Armor Application.....	13
6.5 Armor Corrugation.....	14
6.6 Armor Overlap.....	14
6.7 Armor Splices.....	14
SECTION 7 ELECTRICAL REQUIREMENTS	14
7.1 Requirements.....	14
7.2 Measurement Precaution	14
7.3 DC Resistance	14
7.4 DC Resistance Unbalance	15
7.5 Mutual Capacitance	15
7.6 Pair-to-Pair Capacitance Unbalance	15

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	7.7	Pair-to-Ground Capacitance Unbalance 15
	7.8	Characteristic Impedance 15
	7.9	Return Loss 15
	7.10	Attenuation 16
	7.11	Delay and Differential Delay (Skew) 16
	7.11.1	Delay 17
	7.11.2	Differential Delay (Skew) 17
	7.12	Near End Crosstalk 17
	7.13	Power Sum NEXT 17
	7.14	Far End Crosstalk 18
	7.14.1	ELFEXT 18
	7.14.2	Power Sum ELFEXT 19
	7.15	Phase Velocity 19
	7.16	Insulation Resistance 19
	7.17	Conductor-to-Conductor DC Proof Test 19
	7.18	Core-to-Shield DC Proof Test 20
	7.19	Shield Resistance 20
	7.20	Shield Heating Test 20
	7.21	Fusing Coordination Test 20
	7.22	Continuity of Metallic Wire Elements 20
	SECTION 8	MECHANICAL REQUIREMENTS 21
	8.1	Compound Flow 21
	8.2	Moisture Resistance 21
	8.2.1	Water Penetration 21
	8.2.2	Water Resistance Test 21
	8.3	Wire Bending Test 21
	8.4	Impact Test 21
	8.5	Breaking Force 22
	8.6	Flammability 22
	8.7	Sheath Adherence-Unbonded 22
	SECTION 9	GENERAL REQUIREMENTS 22
	9.1	Identification and Marking 22
	9.1.4	Jacket Marking 23
	9.1.5	Length Marking 23
	9.1.6	Communications Cable Identifier 24

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	9.2 End Sealing	24
	9.3 Packaging	24

TABLES

Table 2 -1	- Nominal Conductor Diameter	3
Table 2 - 2	- Minimum Conductor Elongation	3
Table 3 - 1	- Insulation Colors	5
Table 3 - 2	- Minimum Compressive Strength	6
Table 3 - 3	- Color Coding	7
Table 5 - 1	- Tape Thicknesses	10
Table 6 - 1	- Minimum Jacket Thickness	12
Table 6 - 2	- Completed Wire Material Requirements.....	12
Table 6 - 3	- Steel Composition	13
Table 7 - 1	- DC Resistance	14
Table 7 - 2	- Return Loss Values	15
Table 7 - 3	- Attenuation Coefficients	16
Table 7 - 4	- Attenuation	16
Table 7 - 5	- Worst Pair to Pair NEXT.....	18
Table 7 - 6	- Worst Pair to Pair ELFEXT.....	19
Table 7 - 7	- DC - Proof Test	20
Table 9 - 1	- Year of Manufacture Marker.....	23
Table I	- Specifications Referenced in this Standard.....	25
Table E - 1	- Test Currents and Durations	35

APPENDICES

Appendix A	- Jacket Rip Cord Test.....	31
Appendix B	- Metallic Tape Splice Breaking Strength, Percent Retention	32
Appendix C	- Absorption Coefficient Test for PVC.....	33
Appendix D	- Fusing Coordination Test	35
Appendix E	- Water Resistance Test.....	37

TABLE OF CONTENTS

CONTENTS: SECTION PAGE

FIGURES

FIGURE 1	-	Sheath Adherence Sample Preparation	28
Figure D-1	-	Fusing Coordination Test Configuration	36
Figure E-1	-	Pressure Cell for Water Resistance Test	38

ANNEX

Informative ANNEX A	-	Product Guide for Broadband Buried Service Wires	A-1
Informative ANNEX B	-	ICEA Telecommunication Cable Standards.....	B-1

**ACRONYMS, ABBREVIATIONS AND SYMBOLS
(Used in this Standard)**

A	-	ampere, apparent absorption coefficient or cross sectional area
ac	-	alternating current
ANSI	-	American National Standards Institute
ASTM	-	American Society for Testing and Materials
ATG	-	absorbent thixotropic gel
AWG	-	American Wire Gauge
BB-BSW	-	broadband buried service wire
CAS	-	Chemical Abstract Service
Cg	-	ground component of mutual capacitance
cm	-	centimeter
CUPP	-	capacitance unbalance pair to pair
dB	-	decibel
dc	-	direct current
ECCS	-	electrolytic chrome coated steel
EIA	-	Electronics Industries Alliance
ETPR	-	extended thermoplastic rubber
F	-	constant representing a specific frequency
f	-	variable representing any frequency in the applicable range
ELFEXT	-	equal level far end crosstalk
FEXT	-	far end crosstalk
ft	-	foot, feet
g	-	gram
Hz	-	Hertz
ICEA	-	Insulated Cable Engineers Association
in	-	inch
IOFEXT	-	input to output far end crosstalk
ISO	-	International Organization for Standardization
k1, k2, k3	-	coefficients for calculating attenuation
kft	-	kilofoot
kHz	-	kilo-Hertz
km	-	kilometer
kV	-	kilovolt
L	-	length of wire for which electrical results are reported
l	-	path length of glass cell
lbf	-	pound-force
lm	-	length of wire for which electrical measurements have been made
m	-	meter or index for "measured"
Mb	-	megabit
mg	-	milligram
MHz	-	mega-Hertz
mil	-	thousandths of an inch
ml	-	milliliter
mm	-	millimeter

ACRONYMS, ABBREVIATIONS AND SYMBOLS (cont.)
(Used in this Standard)

MO	-	manufacturers option
MPa	-	mega-Pascal
MΩ	-	meg Ohm
N	-	Newton or number of pairs in wire
NEC	-	National Electrical Code
NESC	-	National Electrical Safety Code
NEXT	-	near end crosstalk
nF	-	nanofarad
NFPA	-	National Fire Protection Association
NID	-	network interface device
nsec	-	nanosecond
oz	-	ounce
PEPJ	-	polyethylene/petroleum jelly
pF	-	picofarad
psi	-	pounds per square inch
PVC	-	polyvinyl chloride
rms	-	root-mean-square value
s	-	second
SI	-	International System of Units
T	-	temperature or percent transmission at a specific wavelength
THF	-	tetrahydrofuran
TIA	-	Telecommunications Industry Association
UL	-	Underwriters Laboratories
Vs	-	volume of stirring bar
W	-	weight of sample
yd	-	yard
°C	-	degree Celsius
°F	-	degree Fahrenheit
α	-	attenuation per unit length
ρ	-	density
Ω	-	Ohm
%	-	percent

(Page intentionally left blank.)

STANDARD FOR BROADBAND BURIED SERVICE WIRE FILLED, POLYOLEFIN INSULATED, COPPER CONDUCTOR

TECHNICAL REQUIREMENTS

SECTION 1 GENERAL

- 1.1 **PURPOSE:** The purpose of this Standard is to establish generic technical requirements that may be referenced by individual telecommunications wire specifications covering products intended to connect the broadband outside plant to the individual customer premises. The parameters covered provide material, construction, and performance requirements.

Because this Standard does not cover all details of individual wire design, it cannot be used as a single document for procurement of product. It is intended to be used in conjunction with an individual product specification that provides complete design details for the specific wire type and designates the applicable performance requirements. Such individual wire specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

The manufacturer and user of these wires should consider the selection and availability of appropriate hardware in the installation of these products

- 1.2 **SCOPE:** This Standard covers material, mechanical and electrical requirements for Broadband Buried Service Wire (BB-BSW) of ≤ 6 pair, intended for use principally in extending a circuit from a broadband cable terminal to a subscriber's network interface device (NID).
- 1.3 **OPTIONS AND INFORMATION:** This Standard provides alternative choices for type of insulation, type of filling compound, sheath design (shielding materials, single or double jackets, and jacket type and thickness) and armoring.

One objective of this Standard is to ensure compatibility with the Category 5e system requirements (except Delay, see 7.11.1) as specified in the TIA/EIA Standard 568-C.2 for commercial building telecommunications cabling, so that the standardized service wires can be used in a "Customer Owned Outside Plant" or as "Campus Cables", provided they have an appropriate pair count.

Broadband buried service wires as described in this Standard are primarily intended to connect the customer premises to a buried broadband outside or distribution plant. As such, this Standard is a complement to the ICEA S-99-689 standard.

This Standard is arranged in Sections covering specific areas of wire requirements and may be referenced as complete Sections or as individual paragraphs.

Sections of this specification where the user may specify a particular option are listed below:

- 2.1 Conductor Size (AWG)
- 3.2 Insulation Type
- 4.4.2 Filling Compound Type
- 4.5 Flooding Compound
- 4.7 Rip Cord(s)
- 5.1 Shielding System
- 6.1 Inner Jacket
- 6.2.1 Outer Jacket (Raw Material)
- 6.3 Armoring Systems
- 7.20 Shield Heating Test
- 7.21 Fusing Coordination Test
- 8.6 Flammability
- 9.1 Identification and Marking
- 9.3 Packaging