

STANDARD FOR
TELECOMMUNICATIONS CABLE
AIRCORE, POLYOLEFIN INSULATED, COPPER CONDUCTOR
TECHNICAL REQUIREMENTS

Published By
INSULATED CABLE ENGINEERS ASSOCIATION, INC.
Post Office Box 1568
Carrollton, GA 30112, U.S.A.

Fifth Edition

© by ICEA

Approved September 14, 2010 by
Insulated Cable Engineers Association, Inc.

Approved 7/15/2011 by ANSI ASC C-8
American National Standards Institute

Copyrighted by the ICEA
Contents may not be reproduced
in any form without permission of the
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

IHS
15 Inverness Way East
Englewood, CO 80112-5776 USA
Telephone: (800) 854-7179
www.ihs.com

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

FOREWORD

ICEA Standards are published in the public interest and are intended to promote product uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to the Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard, hereafter assumes, that manufacture, testing, installation, and maintenance of cables defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions of interpretation of ICEA Standards can only be accepted in writing and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to:

Secretary
Insulated Cable Engineers Association
P.O. Box 1568
Carrollton, GA 30112
United States of America

This Standard was developed by the ICEA Communications Division, WG-625. It was approved by ICEA on September 14, 2010.

The members of the ICEA Communications Cable Division, Working Group 625, who participated in this project, were:

Peter Fraley, Chairman

D. K. Baker
G. Dorna
J. Baer

T. Zou
T. McLaughlin

The following participated in an advisory capacity to WG-625:

Joe Mafnas

RUS

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
1.	GENERAL	
	1.1 Purpose.....	1
	1.2 Scope.....	1
	1.3 Options and Information.....	1
	1.4 Units and Tolerances.....	2
	1.5 References.....	2
	1.6 Quality Assurance.....	2
	1.7 Safety Considerations.....	3
2.	CONDUCTORS	
	2.1 Requirements.....	3
	2.2 Factory Joints.....	4
3.	CONDUCTOR INSULATION	
	3.1 Insulation Materials.....	4
	3.1.1 Propylene/Ethylene Copolymer.....	4
	3.1.2 High-Density Polyethylene.....	4
	3.1.3 Medium-Density Polyethylene.....	4
	3.2 Insulation Type.....	4
	3.2.1 Solid.....	4
	3.2.2 Foam.....	4
	3.2.3 Foam-Skin.....	4
	3.3 Insulation Dimensions, Colors, and Splices.....	4
	3.4 Insulation Physical Requirements.....	5
	3.4.1 Insulation Adhesion.....	5
	3.4.2 Elongation.....	5
	3.4.3 Compression.....	6
	3.4.4 Cold Bend.....	6
	3.4.5 Shrinkback.....	6
	3.4.6 Thermal Oxidative Stability.....	6
	3.5 Twist Length and Color Coding.....	7
4.	CORE CONSTRUCTIONS	
	4.1 Core Assembly.....	7
	4.2 Binders.....	9
	4.3 Spare Pairs.....	10
	4.4 Core Wrap.....	10
	4.5 Self-Support (Figure 8) Cable.....	11
	4.5.1 Support Messenger.....	11
	4.5.2 Undulated Core.....	11

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	4.5.3 Dimensions.....	11
	4.5.4 Reinforced Self-Support	11
	4.6 Flooding Compound.....	11
5.	INTERNAL SCREENS	
	5.1 Description	11
	5.2 Screen Material	12
	5.2.1	
	Film Delamination	12
	5.3 Service Pairs	12
6.	SHIELDS	
	6.1 Shielding Systems.....	12
	6.2 Shield Materials.....	13
	6.2.1 8-mil Bare Aluminum Tape	13
	6.2.2 8-mil Coated Aluminum Tape	13
	6.2.3 5-mil Copper Tape.....	13
	6.2.4 5-mil Copper Clad Alloy Steel Tape.....	13
	6.2.5 5-mil Copper Clad Stainless Steel Tape.....	14
	6.2.6 6- and 7-mil C194 Copper Alloy Tapes	14
	6.2.7 5-mil C230 Copper Alloy Tape	14
	6.2.8 6-mil Bare Steel Tape.....	14
	6.2.9 6-mil Coated Steel Tape.....	15
	6.3 Shield Application.....	15
	6.3.1 Shield Corrugation.....	15
	6.3.2 Residue Forming/Corrugating Oil	15
	6.3.3 Shield Overlap.....	15
	6.3.4 Shield Splices.....	16
	6.4 Corrosion Resistance	16
	6.5 Gopher Resistance Test.....	16
7.	POLYETHYLENE INNER AND OUTER JACKETS	
	7.1 Inner Jacket.....	17
	7.1.1 Material and Test Requirements	17
	7.1.2 Inner Jacket Thickness Requirement	17
	7.2 Outer Jacket.....	18
	7.2.1 Raw Material	18
	7.2.2 Outer Jacket Thickness Requirement.....	18
	7.2.3 Completed Cable Material Requirements.....	19
	7.2.4 Shrinkback.....	21

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	7.2.5 Sheath Adherence - Flooded.....	21
	7.2.6 Sheath Adherence - Bonded	21
8.	ELECTRICAL REQUIREMENTS	
	8.1 DC Resistance	21
	8.2 DC Resistance Unbalance	22
	8.3 Mutual Capacitance.....	22
	8.3.1 Final Product 100% Testing.....	22
	8.4 Pair-to-Pair Capacitance Unbalance	23
	8.5 Pair-to-Ground Capacitance Unbalance.....	23
	8.6 Attenuation	23
	8.7 Unit Crosstalk.....	23
	8.7.1 Crosstalk Qualification Test.....	24
	8.8 Between-Compartment Crosstalk for Screened Cables	25
	8.8.1. Requirements for all Applications	25
	8.8.2 Requirements for T-1C and Similar Applications	25
	8.8.3 Qualification Test Procedure	25
	8.9 Insulation Resistance	26
	8.10 Conductor-To-Conductor DC Proof Test.....	26
	8.10.1 Alternate Test Protocols.....	27
	8.11 Core-To-Shield DC Proof Test	27
	8.12 Core-To-Screen DC Proof Test.....	27
	8.13 Shield Resistance	27
	8.14 Continuity of Metallic Cable Elements.....	27
9.	MECHANICAL REQUIREMENTS	
	9.1 Cable Bend Test	27
	9.1.1 Cold Bend Test.....	27
	9.1.2 Hot Bend Test	28
	9.2 Cable Impact	28
	9.3 Cable Torsion Test.....	28
10.	GENERAL REQUIREMENTS	
	10.1 Identification and Marking	28
	10.1.1 Identification	29
	10.1.2 Length Marking	29
	10.1.3 Defective Pair Marking	30

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	10.1.4 Communication Cable Identifier	30
	10.2 End Sealing	30
	10.3 Information Accompanying the Reel	30
	10.4 Pressurization	31
	10.5 Optional Requirements.....	31
	10.5.1 Physical Reel Protection	31
	10.5.2 Pulling Eyes	31

TABLES

Table 1:	Specifications Referenced in This Standard	32
Table 2-1	Conductor Diameter	3
Table 2-2	Conductor Elongation	4
Table 3-1	Insulation Colors	5
Table 3-2	Conductor Adhesion	5
Table 3-3	Insulation Compression	6
Table 3-4	Pair Designation and Color Code.....	7
Table 4-1	Group Binder Color Code.....	8
Table 4-2	Super-Unit Binder Color Code	9
Table 4-3	Color Code for Spare or Service Pairs	10
Table 6-1	Copper Alloy Tape Minimum Thickness.....	14
Table 6-2	Steel Composition Limits	15
Table 6-3	Shield Tape Tensile Load	16
Table 7-1	Minimum Inner Jacket Thickness.....	18
Table 7-2	Outer Jacket Thicknesses.....	19
Table 7-3	Completed Cable Jacket Material Requirements	20
Table 8-1	Maximum DC Resistance.....	22
Table 8-2	Conductor Resistance Unbalance.....	22
Table 8-3	Mutual Capacitance	22
Table 8-4	Pair-to-Ground Capacitance Unbalance	23
Table 8-5	Average Attenuation	23
Table 8-6	Power Sum Equal Level Far End Crosstalk (PSELFEXT)	24
Table 8-7	Power Sum Near End Crosstalk (PSNEXT).....	24
Table 8-8	Conductor-to-Conductor dc Test Voltages.....	26
Table 10-1	Pulling Eye Load Factor.....	31

TABLE OF CONTENTS

CONTENTS: SECTION PAGE

FIGURES

Figure 1-A:	Polyethylene Jacket Thickness Requirements for Self-Support (Figure 8) Cable - Option A.....	35
Figure 1-B:	Polyethylene Jacket Thickness Requirements for Self-Support (Figure 8) Cable - Option B.....	36
Figure 1-C:	Polyethylene Jacket Thickness Requirements for Reinforced Self-Support (Figure 8) Cable.....	37
Figure 2:	Forming of Steel Tape Overlap.....	38
Figure 3:	Sheath Adherence Sample Preparation.....	41

APPENDICES

Appendix A:	Wicking and Hygroscopicity Test Procedures.....	42
	Figure A-1.....	43
Appendix B:	Excess Core Test Procedure.....	44
	Figure B-1, Excess Core Test Setup.....	45
Appendix C:	Metallic Tape Splice Breaking Strength, Percent Retention.....	47
Appendix D:	Standard Internally Screened (IS) Cable Pair Counts.....	48
Appendix E:	Corrosion Resistance.....	50

ANNEXES

Informative Annex A:	Product Guide.....	A-1
Informative Annex B:	ICEA Telecommunication Cable Standards.....	B-1

ACRONYMS, ABBREVIATIONS AND SYMBOLS

ANSI	American National Standards Institute
ASTM	American Society for Testing and Materials
AWG	American Wire Gauge
°C	Degrees of Temperature, Celsius scale, Centigrade
dB	decibel
dc	Direct Current
EIA	Electronic Industries Alliance
ELFEXT	Equal Level Far-End Crosstalk
°F	Degrees of Temperature, Fahrenheit scale
ft	foot or feet
g	gram
ICEA	Insulated Cable Engineers Association
in	inch
ISO	- International Organization for Standardization
kHz	kilohertz
kV	kilovolt
lb	pounds
lbf	pounds of force
MHz	Megahertz
m	meter
mm	millimeter
MPa	megapascal
N	Newton
nF	nanofarad
NEXT	Near-End Crosstalk
NESC	National Electrical Safety Code
ns	nanoseconds
pF	picofarad
PSELFEXT	power sum equal level far end crosstalk
PSNEXT	power sum near end crosstalk
psi	pounds per square inch
rms	root mean square
α	Attenuation

ICEA STANDARD FOR AIRCORE, POLYOLEFIN INSULATED, COPPER CONDUCTOR TELECOMMUNICATIONS CABLE TECHNICAL REQUIREMENTS

SECTION 1 GENERAL

- 1.1 **PURPOSE:** The purpose of this Standard is to establish generic technical requirements that may be referenced by individual telecommunications cable specifications covering products intended for normal outside plant use. The parameters covered provide material, construction, and performance requirements that are applicable to aircore, polyolefin insulated and jacketed cables of all pair counts, including a variety of shield and jacket combinations and optional compartmental screening.

Because this Standard does not cover all details of individual cable design, it cannot be used as a single document for procurement of product. It is intended to be used in conjunction with an individual product specification that provides complete design details for the specific cable type and designates the applicable performance requirements. Such individual cable specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

- 1.2 **SCOPE:** This Standard covers mechanical and electrical requirements for aircore, polyolefin insulated, copper conductor telecommunications cable. It provides alternative choices for type of insulation, core assembly, color code, sheath design (shielding materials, single or double jackets, and jacket thickness), and screened or non-screened core.
- 1.3 **OPTIONS AND INFORMATION:** These cables are traditional outside plant (OSP) cables having a nominal mutual capacitance at 1 kHz of 52 nF/km (83 nF/mile), with attenuation and crosstalk characterized at discrete frequencies up to 6.3 MHz. For cables characterized above 6.3 MHz, refer to ICEA S-99-688, Broadband Twisted Pair Cable, Aircore, Polyolefin Insulated, Copper Conductors.

This Standard is arranged in Sections. Each covers one specific area of cable requirement and may be referenced as complete Sections or as individual paragraphs.