

**ICEA STANDARD FOR  
COAXIAL AND COAXIAL/TWISTED PAIR  
COMPOSITE BURIED SERVICE WIRES  
TECHNICAL REQUIREMENTS**

Published By

**INSULATED CABLE ENGINEERS ASSOCIATION, INC.**

Post Office Box 1568

Carrollton, Georgia 30112, U.S.A.

© 2006 by ICEA

Approved January 27, 2006 by  
Insulated Cable Engineers Association, Inc.

Approved April 25, 2006 by  
American National Standards Institute, Inc.

Copyrighted by the ICEA  
Contents may not be reproduced  
in any form without permission of the  
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

GLOBAL ENGINEERING DOCUMENTS  
15 Inverness Way East  
Englewood, CO 80113-5776 USA  
Telephone: (800) 854-7179  
[www.global.ihs.com](http://www.global.ihs.com)

## NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgements contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgement or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certifications or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

(page intentionally left blank)

## FOREWORD

ICEA Standards are published in the public interest and are intended to promote uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to this Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard hereafter assumes that manufacture, testing, installation, and maintenance of cables defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions for interpretation of ICEA Standards can only be accepted in writing and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to:

Secretary  
 Insulated Cable Engineers Association, Inc.  
 Post Office Box 1568  
 Carrollton, GA 30112, U.S.A.  
 United States of America

This Standard was approved by ICEA on January 27, 2006. The members of the ICEA Communications Cable Section, Working Group 674, who participated in this project, were:

D. K. Baker  
 J. Kincaid

L. Hazy  
 B. Pope

T. Zou  
 K. Chauvin

The following participated in an advisory capacity to Working Group 674:

G. Hessler            RUS

(page intentionally left blank)

**TABLE OF CONTENTS**

CONTENTS	SECTION	PAGE
1	<u>GENERAL</u>	
	1.1 Purpose.....	1
	1.2 Scope.....	1
	1.3 Options and Information.....	1
	1.4 Units And Tolerances.....	2
	1.5 References.....	2
	1.6 Quality Assurance.....	2
	1.7 Safety Considerations.....	3
2	<u>CONDUCTORS</u>	
	2.1 Twisted Pair Conductors.....	3
	2.1.1 Requirements.....	3
	2.1.2 Factory Joints.....	3
	2.2 Conductors of Coaxial Unit.....	3
	2.2.1 Center Conductor of Coaxial Unit.....	3
	2.2.1.1 Resistance Requirements.....	3
	2.2.1.2 Tensile and Elongation Requirements.....	4
	2.2.1.3 Factory Joints.....	4
	2.2.2 Outer Conductor (Shield) of Coaxial Unit.....	4
	2.2.2.1 Shielding Tape.....	5
	2.2.2.2 Braid.....	5
	2.2.2.3 Outer Shield.....	6
	2.2.2.4 Outer Braid.....	6
3	<u>CONDUCTOR INSULATION</u>	
	3.1 Conductor Insulation for Twisted Pairs.....	6
	3.1.1 Insulation Material.....	6
	3.1.2 Insulation Type.....	6
	3.1.3 Insulation Dimensions and Colors.....	6
	3.1.4 Splices.....	7
	3.1.5 Insulation Physical Requirements.....	7
	3.1.5.1 Adhesion.....	7
	3.1.5.2 Elongation.....	7
	3.1.5.3 Compression.....	7
	3.1.5.4 Cold bend.....	7
	3.1.5.5 Shrinkback.....	7
	3.1.5.6 Thermal Oxidative Stability.....	8
	3.1.6 Spark Test.....	8
	3.1.7 Twist Length and Color Coding.....	8

**TABLE OF CONTENTS**

CONTENTS	SECTION	PAGE
	3.2	Conductor Insulation for Center Conductor of Coaxial Unit ..... 9
	3.2.1	Insulation Material ..... 9
	3.2.2	Insulation Type ..... 9
	3.2.3	Insulation Dimension ..... 9
	3.2.4	Insulation Physical Requirements ..... 9
	3.2.4.1	Adhesion ..... 9
	3.2.4.2	Thermal Oxidative Stability OIT Test of Foam Dielectric ..... 10
	3.2.4.3	Shrinkback ..... 10
4	<b><u>CORE CONSTRUCTION</u></b>	
	4.1	Coaxial Unit ..... 10
	4.1.1	Jacket Material ..... 10
	4.1.2	Jacket Thickness ..... 10
	4.1.3	Jacket Eccentricity ..... 10
	4.1.4	Diameter Over Coax-Jacket ..... 11
	4.1.5	Completed Wire Jacket Requirements ..... 12
	4.1.5.1	Tensile Strength ..... 12
	4.1.5.2	Elongation ..... 12
	4.2	Composite Core Lay Up ..... 12
	4.3	Binders ..... 13
	4.4	Core Wrap ..... 13
	4.5	Rip Cord(s) ..... 13
	4.6	Filling Compound ..... 14
	4.6.1	Filling Compound Type ..... 14
	4.6.2	Adequacy of Fill ..... 14
	4.7	Flooding Compound ..... 14
	4.8	Water Swellable Materials ..... 14
5	<b><u>SHIELDS</u></b>	
	5.1	General ..... 14
	5.2	Shielding System ..... 15
	5.2.1	Gopher Shields ..... 15
	5.2.2	Non-Gopher Shields ..... 15
	5.3	Shield Materials ..... 15
	5.3.1	5- or 6-Mil Copper Clad Stainless Steel Tape ..... 15
	5.3.2	5- or 6-Mil Copper Clad Alloy Steel Tape ..... 15
	5.3.3	5-mil C230 Copper Alloy ..... 16
	5.3.4	6-Mil C195 Copper Alloy Tape ..... 16
	5.3.5	5.5-Mil C664 Copper Alloy Tape ..... 16
	5.3.6	7-Mil C194 Copper Alloy Tape ..... 16
	5.3.7	4- or 5-Mil C220 Copper Alloy Tape ..... 16



## TABLE OF CONTENTS

CONTENTS	SECTION	PAGE
	5.3.8 8-Mil Coated Aluminum Tape.....	16
	5.4 Shield Application .....	16
	5.5 Shield Corrugation .....	16
	5.6 Shield Overlap .....	17
	5.7 Shield Splices .....	17
	5.8 Unshielded Constructions .....	17
6	<u>INNER AND OUTER JACKET, ARMORING SYSTEMS</u>	
	6.1 Inner Jacket .....	17
	6.1.1 Materials and Test Requirements .....	17
	6.1.2 Inner Jacket Thickness Requirements .....	17
	6.2 Outer Jacket.....	18
	6.2.1 Raw Material .....	18
	6.2.2 Outer Jacket Thickness Requirement .....	18
	6.2.3 Completed Wire Material Requirement .....	19
	6.2.4 Shrinkback .....	20
	6.3 Armoring Systems.....	20
	6.3.1 6-Mil Bare Steel Tape .....	20
	6.3.2 6-Mil Coated Steel Tape .....	21
	6.3.3 Galvanized Steel Strip.....	21
	6.3.4 4- or 5-Mil 302 or 304 Stainless Steel Tape .....	21
	6.4 Armor Application.....	21
	6.5 Armor Corrugation .....	21
	6.6 Armor Overlap.....	22
	6.7 Armor Splices.....	22
7	<u>ELECTRICAL REQUIREMENTS</u>	
	General.....	22
	7.1 Electrical Requirements of Twisted Pairs .....	22
	7.1.1 Continuity .....	22
	7.1.2 Conductor Resistance.....	22
	7.1.3 Resistance Unbalance .....	22
	7.1.4 Mutual Capacitance .....	22
	7.1.5 Pair-To-Pair Capacitance Unbalance.....	22
	7.1.6 Pair-To-Ground Capacitance Unbalance .....	22
	7.1.7 Attenuation .....	23
	7.1.8 Crosstalk .....	23
	7.1.9 Insulation Resistance .....	23
	7.1.10 Conductor-To-Conductor DC Proof Test.....	23
	7.1.11 Core-To-Shield DC Proof Test .....	23
	7.1.12 Shield Resistance .....	23
	7.1.13 Shield Heating Test.....	24
	7.1.14 Fusing Coordination .....	24

**TABLE OF CONTENTS**

CONTENTS	SECTION	PAGE
	7.2 Electrical Requirements Of Coaxial Unit.....	24
	7.2.1 Continuity .....	24
	7.2.2 Conductor Resistance .....	24
	7.2.3 Insulation Resistance .....	24
	7.2.4 Dielectric Strength .....	24
	7.2.5 Characteristic Impedance .....	25
	7.2.6 Structural Return Loss .....	25
	7.2.7 Shielding Effectiveness .....	25
	7.2.8 Attenuation .....	25
	7.2.9 Velocity of Propagation .....	26
	7.2.10 Heat Aging Test .....	26
	7.3 Unshielded Buried Service Wire .....	27
8	<b><u>REQUIREMENTS OF COMPLETED WIRE</u></b>	
	8.1 Compound Flow .....	27
	8.2 Water Penetration (Fully Flooded Design).....	27
	8.3 Water Resistance Test (Non-Fully Flooded Design).....	27
	8.4 Mechanical Requirements .....	27
	8.4.1 Impact Test .....	28
	8.4.2 Wire Bending Test.....	28
	8.4.2.1 Cold Bend Test .....	28
	8.4.2.2 Hot Bend Test .....	28
	8.4.3 Breaking Force .....	28
	8.4.4 Sheath Adherence - Unbonded.....	28
	8.4.5 Toughness (Inner Jacket, Core Wrap) .....	28
	8.4.5.1 Puncture Test .....	29
	8.4.5.2 Cut-Through Test .....	29
	8.5 Environmental Requirements.....	29
	8.5.1 Cold Temperature Handling .....	29
	8.5.2 Separation Along The Web .....	29
	8.5.2.1 Room Temperature Separation .....	29
	8.5.2.2 Low Temperature Separation .....	29
	8.6 Flammability .....	30
	8.7 National Electric Code .....	30
9	<b><u>MARKING AND PACKAGING</u></b>	
	9.1 Identification and Marking .....	30
	9.1.1 Manufacturer Identification .....	30
	9.1.2 Year of Manufacture.....	30
	9.1.3 Alternate Identification.....	31
	9.1.4 Jacket Marking .....	31

## TABLE OF CONTENTS

CONTENTS	SECTION	PAGE
	9.1.5 Length Marking .....	31
	9.1.6 Jacket Ink Marking Durability .....	32
	9.1.7 Communications Identifier.....	32
	9.2 End-Sealing .....	32
	9.3 Thermal Wrap .....	32
	9.4 Packaging .....	33

### TABLES

Table 2-1: Conductivity and DC Resistance of Center Conductor – Coaxial Unit .....	4
Table 2-2: Elongation and Tensile Strength of Center Conductor – Coaxial Unit .....	4
Table 2-3: Diameter of Outer Conductor – Coaxial Unit.....	5
Table 3-1: Conductor Insulation Color – Twisted Pairs .....	7
Table 3-2: Twisted Pair Color Code .....	8
Table 3-3: Diameter and Eccentricity of Center Conductor Insulation – Coaxial Unit.....	9
Table 3-4: Center Conductor Insulation Adhesion – Coaxial Unit .....	9
Table 4-1: Diameter Over Jacket – Coaxial Unit .....	12
Table 5-1: Copper Clad Stainless Steel Tape Thickness .....	15
Table 5-2: C220 Copper Alloy Tape Thickness.....	16
Table 6-1: Outer Jacket Thickness – Completed Wire .....	19
Table 6-2: Completed Wire Material Requirements .....	19
Table 6-3: Steel Tape Composition.....	20
Table 6-4: 304 and 305 Stainless Steel Tape Thickness .....	21
Table 7-1: Attenuation Requirements – Twisted Pairs .....	23
Table 7-2: Conductor-To-Conductor DC Proof Test.....	23
Table 7-3: Loop Resistance – Coaxial Unit .....	24
Table 7-4: Attenuation Requirements – Coaxial Unit .....	26
Table 9-1: Year Of Manufacture Marker Threads .....	31
Table I: Specifications Referenced in this Standard .....	34
Table E-1: Test Current and Current Duration – Fusing Coordination Test .....	47

### FIGURES

Figure 4-1: Jacket Thickness Measurement Method Standard and Quad Shielded Coaxial Wires .....	11
Figure 4-2: Joint Core and Figure 8 Design .....	13
Figure 1: Sheath Adherence Sample Preparation .....	38
Figure 2: Puncture Test Configuration.....	39
Figure 3: Cut-Through Test Configuration .....	40
Figure A-1: Wicking Test Configuration.....	42
Figure E-1: Fusing Coordination Test Configuration .....	48
Figure F-1: Pressure Cell For Water Resistance Test .....	50

**TABLE OF CONTENTS**

CONTENTS	SECTION	PAGE
----------	---------	------

**APPENDICES**

Appendix A	Test Procedure For Wicking .....	41
Appendix B	Jacket Rip Cord Test.....	43
Appendix C	Metallic Tape Splice Breaking Strength, Percent Retention.....	44
Appendix D	Absorption Coefficient Test For PVC.....	45
Appendix E	Fusing Coordination Test .....	47
Appendix F	Water Resistance Test .....	49

**INFORMATIVE ANNEXES**

INFORMATIVE Annex A	Product Guide .....	A-1
INFORMATIVE Annex B	ICEA Telecommunications Cable Standards.....	B-1

## ACRONYMS, ABBREVIATIONS AND SYMBOLS

A	ampere
ac	alternating current
AISI	American Iron and Steel Institute
ANSI	American National Standards Institute
ASTM	American Society for Testing and Materials
AWG	American Wire Gauge
°C	degrees of temperature, Celsius scale
CAS	Chemical Abstract Services
cc	cubic centimeter
Cg	capacitance-to-ground
cm	centimeter
Cu	chemical symbol for copper
dB	decibels
dc	direct current
ECCS	electrolytic chrome coated steel
EIA	Electronics Industry Alliance
°F	degrees of temperature, Fahrenheit scale
ft	foot or feet
ft <sup>2</sup>	square foot or feet
g	gram
Hz	Hertz
IACS	International Annealed Copper Standard
ICEA	Insulated Cable Engineers Association
in	inch
in <sup>2</sup>	square inch
ISDN	intergrated services digital network
ISO	International Organization for Standardization
kft	kilofoot or kilofeet
kg	kilogram
kHz	kilohertz
km	kilometer
kPa	kilopascal
kV	kilovolt
LAN	local area network
lb	pound
lbf	pound of force
m	meter
m <sup>2</sup>	square meter
Mb	megabit
mg	milligram
MHz	megahertz
min.	minute
ml	milliliter
mm	millimeter

## ACRONYMS, ABBREVIATIONS AND SYMBOLS – (continued)

mm <sup>2</sup>	square millimeter
MPa	megapascal
N	Newton
NEC	National Electrical Code
NESC	National Electrical Safety Code
nF	nanofarad
NID	network interface device
NIU	network interface unit
oz	ounce
%	percent
pF	picofarad
POTS	plain old telephone service
psi	pounds per square inch
PVC	polyvinyl chloride
RF	radio frequency
rms	root-mean-square
SCTE	Society of Cable Telecommunication Engineers
sec	second
T1	North American digital hierarchy line code – equivalent to 1.544 Mb/sec
UL	Underwriters Laboratories
WAN	wide area network
°	degrees symbol, temperature or angle

## COAXIAL AND COAXIAL/TWISTED PAIR COMPOSITE BURIED SERVICE WIRES TECHNICAL REQUIREMENTS

### Section 1 GENERAL

- 1.1 **PURPOSE:** The purpose of this Standard is to establish generic technical requirements that may be referenced by individual telecommunications wire specifications covering products intended for buried outside plant use. The parameters covered provide material, construction, and performance requirements.

Because this Standard does not cover all details of individual wire designs, it cannot be used as a single document for procurement of product. This Standard is intended to be used in conjunction with an individual product specification that provides complete design details for the specific wire type and designates the applicable performance requirements. Such individual wire specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

- 1.2 **SCOPE:** This Standard covers mechanical and electrical requirements of service wires containing at least one coaxial core and optionally up to six twisted pairs, used for service applications to extend the telephone/multimedia circuit from the distribution terminal to the subscriber's station protected  $\neq$  NID (Network Interface Device) or protected NIU (Network Interface Unit).

Furthermore, a distinction between **Type I** and **Type II** is made with regard to transmission characteristics and shielding materials of the coaxial unit.

Buried Service Wire is used to extend buried telephone plant from the distribution cable to the subscriber.

The coaxial unit is intended to be used for either RF or compressed digital video and radio transmissions. This unit shall also allow bi-directional traffic. The coaxial unit should also be capable of carrying high speed digital signals for LAN/WAN applications (such as T1, ISDN, etc.) as well as POTS (Plain Old Telephone Services). The network supporting these protocols will be based upon physical lines having a characteristic impedance of 75 Ohms. The coaxial units are specified in three and four common sizes for **Type I** and **Type II** respectively, to accommodate different drop lengths.

The twisted pair wires are intended for voice and data transmission and their characteristics are based upon existing system requirements and projected application needs.

- 1.3 **OPTIONS AND INFORMATION:**

This Standard is arranged in Sections covering specific areas of wire requirements and may be referenced as complete Sections or as individual paragraphs.